

# POWERS POWERFOAM

Chemwatch Material Safety Data Sheet  
Issue Date: 20-Sep-2006  
NC317ECP

CHEMWATCH 4727-96  
CD 2006/3 Page 1 of 14

---

## Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

---

### PRODUCT NAME

POWERS POWERFOAM

### SYNONYMS

### PROPER SHIPPING NAME

AEROSOLS

### PRODUCT USE

Used according to manufacturer' s directions. Application is by spray atomisation from a hand held aerosol pack.

### SUPPLIER

Company: Powers Fasteners Australasia Pty Ltd

Address:

Factory 3, 205 Abbotts Road

Dandenong South

VIC 3175

Australia

Telephone: +61 3 8787 5888

Telephone: 1800 677 872 (freecall)

Fax: +61 3 8787 5899

---

## Section 2 - HAZARDS IDENTIFICATION

---

### STATEMENT OF HAZARDOUS NATURE

**HAZARDOUS SUBSTANCE. DANGEROUS GOODS.** According to the Criteria of NOHSC, and the ADG Code.

### POISONS SCHEDULE

None

### RISK

Extremely flammable.  
Harmful by inhalation.

Irritating to eyes, respiratory system and skin.

May cause SENSITISATION by inhalation.  
May cause SENSITISATION by skin contact.

Risk of explosion if heated under confinement.

### SAFETY

Keep container in a well ventilated place.  
Avoid exposure - obtain special instructions before use.

To clean the floor and all objects contaminated by this material, use water and detergent.

Keep container tightly closed.

Keep away from food, drink and animal feeding stuffs.

Take off immediately all contaminated clothing.  
In case of contact with eyes, rinse with plenty of water and contact Doctor or Poisons Information Centre.

If swallowed, IMMEDIATELY contact Doctor or

continued...

# POWERS POWERFOAM

Chemwatch Material Safety Data Sheet  
Issue Date: 20-Sep-2006  
NC317ECP

CHEMWATCH 4727-96  
CD 2006/3 Page 2 of 14  
Section 2 - HAZARDS IDENTIFICATION

Poisons Information Centre (show this container or label).  
This material and its container must be disposed of as hazardous waste.

## Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
polymeric diphenylmethane diisocyanate	9016-87-9	>25
dimethyl ether	115-10-6	1-15
hydrocarbon propellant	68476-85-7.	1-10

## Section 4 - FIRST AID MEASURES

### SWALLOWED

- Not considered a normal route of entry.
- If swallowed do NOT induce vomiting.
  - If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
  - Observe the patient carefully.
  - Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.
  - Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.
  - Seek medical advice.

### EYE

- If aerosols come in contact with the eyes:
- Immediately hold the eyelids apart and flush the eye continuously for at least 15 minutes with fresh running water.
  - Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
  - Transport to hospital or doctor without delay.
  - Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

### SKIN

- If solids or aerosol mists are deposited upon the skin:
- Flush skin and hair with running water (and soap if available).
  - Remove any adhering solids with industrial skin cleansing cream.
  - DO NOT use solvents.
  - Seek medical attention in the event of irritation.

### INHALED

- If aerosols, fumes or combustion products are inhaled:
- Remove to fresh air.
  - Lay patient down. Keep warm and rested.
  - Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
  - If breathing is shallow or has stopped, ensure clear airway and apply resuscitation, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.

continued...

# POWERS POWERFOAM

Chemwatch Material Safety Data Sheet

Issue Date: 20-Sep-2006

NC317ECP

CHEMWATCH 4727-96

CD 2006/3 Page 3 of 14

Section 4 - FIRST AID MEASURES

- 
- Transport to hospital, or doctor.

## NOTES TO PHYSICIAN

Treat symptomatically.

For sub-chronic and chronic exposures to isocyanates:

- This material may be a potent pulmonary sensitiser which causes bronchospasm even in patients without prior airway hyperreactivity.
- Clinical symptoms of exposure involve mucosal irritation of respiratory and gastrointestinal tracts.
- Conjunctival irritation, skin inflammation (erythema, pain vesiculation) and gastrointestinal disturbances occur soon after exposure.
- Pulmonary symptoms include cough, burning, substernal pain and dyspnoea.
- Some cross-sensitivity occurs between different isocyanates.
- Noncardiogenic pulmonary edema and bronchospasm are the most serious consequences of exposure. Markedly symptomatic patients should receive oxygen, ventilatory support and an intravenous line.
- Treatment for asthma includes inhaled sympathomimetics (epinephrine [adrenalin], terbutaline) and steroids.
- Activated charcoal (1 g/kg) and a cathartic (sorbitol, magnesium citrate) may be useful for ingestion.
- Mydriatics, systemic analgesics and topical antibiotics (Sulamyd) may be used for corneal abrasions.
- There is no effective therapy for sensitised workers.

[Ellenhorn and Barceloux; Medical Toxicology]

NOTE: Isocyanates cause airway restriction in naive individuals with the degree of response dependant on the concentration and duration of exposure. They induce smooth muscle contraction which leads to bronchoconstrictive episodes. Acute changes in lung function, such as decreased FEV1, may not represent sensitivity.

[Karol & Jin, Frontiers in Molecular Toxicology, pp 56-61, 1992].

---

## Section 5 - FIRE FIGHTING MEASURES

---

### EXTINGUISHING MEDIA

SMALL FIRE:

- Water spray, dry chemical or CO2

LARGE FIRE:

- Water spray or fog.

### FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.
- If safe, switch off electrical equipment until vapour fire hazard removed.
- Use water delivered as a fine spray to control fire and cool adjacent area.
- DO NOT approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.
- Equipment should be thoroughly decontaminated after use.

When any large container (including road and rail tankers) is involved in a fire, consider evacuation by 100 metres in all directions.

continued...

# POWERS POWERFOAM

Chemwatch Material Safety Data Sheet

Issue Date: 20-Sep-2006

NC317ECP

CHEMWATCH 4727-96

CD 2006/3 Page 4 of 14

Section 5 - FIRE FIGHTING MEASURES

---

## FIRE/EXPLOSION HAZARD

- Liquid and vapour are flammable.
- Moderate fire hazard when exposed to heat or flame.
- Vapour forms an explosive mixture with air.
- Moderate explosion hazard when exposed to heat or flame.
- Vapour may travel a considerable distance to source of ignition.
- Heating may cause expansion or decomposition leading to violent rupture of containers.
- Aerosol cans may explode on exposure to naked flame.
- Rupturing containers may rocket and scatter burning materials.
- Hazards may not be restricted to pressure effects.
- May emit acrid, poisonous or corrosive fumes.
- On combustion, may emit toxic fumes of carbon monoxide (CO).

Combustion products include: carbon dioxide (CO<sub>2</sub>), isocyanates, and minor amounts of, hydrogen cyanide, nitrogen oxides (NO<sub>x</sub>), other pyrolysis products typical of burning organic material.

## FIRE INCOMPATIBILITY

Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result.

## HAZCHEM: 2Y

### Personal Protective Equipment

Breathing apparatus.

Gas tight chemical resistant suit.

Limit exposure duration to 1 BA set 30 mins.

---

## Section 6 - ACCIDENTAL RELEASE MEASURES

---

## EMERGENCY PROCEDURES

### MINOR SPILLS

- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Wear protective clothing, impervious gloves and safety glasses.
- Shut off all possible sources of ignition and increase ventilation.
- Wipe up.
- If safe, damaged cans should be placed in a container outdoors, away from all ignition sources, until pressure has dissipated.
- Undamaged cans should be gathered and stowed safely.

### MAJOR SPILLS

- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water courses.
- No smoking, naked lights or ignition sources.
- Increase ventilation.
- Stop leak if safe to do so.
- Water spray or fog may be used to disperse / absorb vapour.
- Absorb or cover spill with sand, earth, inert materials or vermiculite.
- If safe, damaged cans should be placed in a container outdoors, away from ignition sources, until pressure has dissipated.

continued...

# POWERS POWERFOAM

Chemwatch Material Safety Data Sheet

Issue Date: 20-Sep-2006

NC317ECP


CHEMWATCH 4727-96

CD 2006/3 Page 5 of 14

Section 6 - ACCIDENTAL RELEASE MEASURES

- Undamaged cans should be gathered and stowed safely.
- Collect residues and seal in labelled drums for disposal.

## PROTECTIVE ACTIONS FOR SPILL



From IERG (Canada/Australia)

Isolation Distance

-

Downwind Protection Distance

8 metres

IERG Number

49

## FOOTNOTES

- 1 PROTECTIVE ACTION ZONE is defined as the area in which people are at risk of harmful exposure. This zone assumes that random changes in wind direction confines the vapour plume to an area within 30 degrees on either side of the predominant wind direction, resulting in a crosswind protective action distance equal to the downwind protective action distance.
- 2 PROTECTIVE ACTIONS should be initiated to the extent possible, beginning with those closest to the spill and working away from the site in the downwind direction. Within the protective action zone a level of vapour concentration may exist resulting in nearly all unprotected persons becoming incapacitated and unable to take protective action and/or incurring serious or irreversible health effects.
- 3 INITIAL ISOLATION ZONE is determined as an area, including upwind of the incident, within which a high probability of localised wind reversal may expose nearly all persons without appropriate protection to life-threatening concentrations of the material.
- 4 SMALL SPILLS involve a leaking package of 200 litres (55 US gallons) or less, such as a drum (jerrican or box with inner containers). Larger packages leaking less than 200 litres and compressed gas leaking from a small cylinder are also considered "small spills".  
LARGE SPILLS involve many small leaking packages or a leaking package of greater than 200 litres, such as a cargo tank, portable tank or a "one-tonne" compressed gas cylinder.
- 5 Guide 126 is taken from the US DOT emergency response guide book.
- 6 IERG information is derived from CANUTEC - Transport Canada.

## EMERGENCY RESPONSE PLANNING GUIDELINES (ERPG)

The maximum airborne concentration below which it is believed that nearly all individuals could be exposed for up to one hour WITHOUT experiencing or developing

life-threatening health effects is:

dimethyl ether	60000 ppm
hydrocarbon propellant	2000 ppm

irreversible or other serious effects or symptoms which could impair an individual's ability to take protective action is:

dimethyl ether	50000 ppm
hydrocarbon propellant	2000 ppm

continued...

# POWERS POWERFOAM

Chemwatch Material Safety Data Sheet

Issue Date: 20-Sep-2006

NC317ECP

CHEMWATCH 4727-96

CD 2006/3 Page 6 of 14

Section 6 - ACCIDENTAL RELEASE MEASURES

---

other than mild, transient adverse effects without perceiving a clearly defined odour is:

dimethyl ether	3000 ppm
hydrocarbon propellant	2000 ppm

The threshold concentration below which most people will experience no appreciable risk of health effects:

dimethyl ether	1000 ppm
hydrocarbon propellant	1000 ppm

American Industrial Hygiene Association (AIHA)

Ingredients considered according to the following cutoffs

Very Toxic (T+)	>= 0.1%	Toxic (T)	>= 3.0%
R50	>= 0.25%	Corrosive (C)	>= 5.0%
R51	>= 2.5%		
else	>= 10%		

where percentage is percentage of ingredient found in the mixture

**Personal Protective Equipment advice is contained in Section 8 of the MSDS.**

---

## Section 7 - HANDLING AND STORAGE

---

### PROCEDURE FOR HANDLING

- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.
- DO NOT enter confined spaces until atmosphere has been checked.
- Avoid smoking, naked lights or ignition sources.
- Avoid contact with incompatible materials.
- When handling, DO NOT eat, drink or smoke.
- DO NOT incinerate or puncture aerosol cans.
- DO NOT spray directly on humans, exposed food or food utensils.
- Avoid physical damage to containers.
- Always wash hands with soap and water after handling.
- Work clothes should be laundered separately.
- Use good occupational work practice.
- Observe manufacturer's storing and handling recommendations.
- Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.

### SUITABLE CONTAINER

- Aerosol dispenser.
- Check that containers are clearly labelled.

### STORAGE INCOMPATIBILITY

Avoid reaction with oxidising agents.

### STORAGE REQUIREMENTS

- Keep dry to avoid corrosion of cans. Corrosion may result in container perforation and internal pressure may eject contents of can.
- Store in original containers in approved flammable liquid storage area.
  - DO NOT store in pits, depressions, basements or areas where vapours may be trapped.

continued...

# POWERS POWERFOAM

Chemwatch Material Safety Data Sheet

Issue Date: 20-Sep-2006

NC317ECP

CHEMWATCH 4727-96

CD 2006/3 Page 7 of 14

Section 7 - HANDLING AND STORAGE

- No smoking, naked lights, heat or ignition sources.
- Keep containers securely sealed. Contents under pressure.
- Store away from incompatible materials.
- Store in a cool, dry, well ventilated area.
- Avoid storage at temperatures higher than 40 deg C.
- Store in an upright position.
- Protect containers against physical damage.
- Check regularly for spills and leaks.
- Observe manufacturer's storing and handling recommendations.

## Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

### EXPOSURE CONTROLS

Source	Material	TWA ppm	TWA mg/m <sup>3</sup>	STEL ppm	STEL mg/m <sup>3</sup>	Peak ppm	Peak mg/m <sup>3</sup>	TWA F/CC
Australia Exposure Standards	dimethyl ether (Dimethyl ether)	400	760	500	950			
Australia Exposure Standards	hydrocarbon propellant (LPG (liquified petroleum gas))	1, 000	1, 800					

The following materials had no OELs on our record under the following CAS or Chemwatch (CW) numbers

- Powers Powerfoam CW:4727-96
- polymeric diphenylmethane diisocyanate: No data available for CAS:9016-87-9
- hydrocarbon propellant: No data available for CAS:68476-86-8

### EMERGENCY EXPOSURE LIMITS

Material	Revised IDLH Value (mg/m3)	Revised IDLH Value (ppm)
hydrocarbon propellant		2, 000 [LEL]

### NOTES

Values marked LEL indicate that the IDLH was based on 10% of the lower explosive limit for safety considerations even though the relevant toxicological data indicated that irreversible health effects or impairment of escape existed only at higher concentrations.

### ODOUR SAFETY FACTOR (OSF)

OSF=0.16 (hydrocarbon propellant)

Exposed individuals are NOT reasonably expected to be warned, by smell, that the Exposure Standard is being exceeded.

Odour Safety Factor (OSF) is determined to fall into either Class C, D or E.

The Odour Safety Factor (OSF) is defined as:

OSF= Exposure Standard (TWA) ppm/ Odour Threshold Value (OTV) ppm

Classification into classes follows:

Class	OSF	Description
A	550	Over 90% of exposed individuals are aware by smell

continued...

# POWERS POWERFOAM

Chemwatch Material Safety Data Sheet

Issue Date: 20-Sep-2006

NC317ECP

CHEMWATCH 4727-96

CD 2006/3 Page 8 of 14

## Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

		that the Exposure Standard (TLV- TWA for example) is being reached, even when distracted by working activities
B	26- 550	As " A" for 50- 90% of persons being distracted
C	1- 26	As " A" for less than 50% of persons being distracted
D	0.18- 1	10- 50% of persons aware of being tested perceive by smell that the Exposure Standard is being reached
E	<0.18	As " D" for less than 10% of persons aware of being tested

### INGREDIENT DATA

#### POLYMERIC DIPHENYLMETHANE DIISOCYANATE:

Some jurisdictions require that health surveillance be conducted on occupationally exposed workers. This should emphasise:

- demography, occupational and medical history and health advice
- completion of a standardised respiratory questionnaire
- physical examination of the respiratory system and skin
- standardised respiratory function tests such as FEV1, FVC and FEV1/FVC.

#### DIMETHYL ETHER:

The no-effect-level for dimethyl ether is somewhere between 2000 ppm (rabbits) and 50,000 ppm (humans) with possible cardiac sensitisation occurring around 200,000 ppm (dogs). The AIHA has adopted a safety factor of 100 in respect to the 50,000 ppm level in its recommendation for a workplace environmental exposure level (WEEL) which is thought to protect against both narcotic and sensitising effects. This level is consistent with the TLV-TWA of 400 ppm for diethyl ether and should be easily achievable using current technologies. The use of the traditionally allowable excursion of 1.25 to the level of 6.25 ppm is felt to be more than adequate as an upper safe limit of exposure.

Human data:

50,000 ppm (12 mins): Feelings of mild intoxication.

75,000 ppm (12 mins): As above plus slight lack of attenuation.

82,000 ppm (12 mins): Some incoordination, slight blurring of vision (30 mins): As above plus analgesia of the face and rushing of blood to the face.

100,000 ppm (10-20 mins): Narcotic symptoms

(64 mins) : Sickness (assumed to be nausea)

144,000 ppm (36 mins): Unconsciousness

#### HYDROCARBON PROPELLANT:

### PERSONAL PROTECTION

#### EYE

- Safety glasses with side shields.
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and

continued...

# POWERS POWERFOAM

Chemwatch Material Safety Data Sheet

Issue Date: 20-Sep-2006

NC317ECP

CHEMWATCH 4727-96

CD 2006/3 Page 9 of 14

## Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

### HANDS/FEET

No special equipment needed when handling small quantities.

#### OTHERWISE:

For potentially moderate exposures:

Wear general protective gloves, eg. light weight rubber gloves.

For potentially heavy exposures:

Wear chemical protective gloves, eg. PVC. and safety footwear.

NOTE: The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.

### OTHER

No special equipment needed when handling small quantities.

#### OTHERWISE:

- Overalls.
- Skin cleansing cream.
- Eyewash unit.
- Do not spray on hot surfaces.

### RESPIRATOR

Selection of the Class and Type of respirator will depend upon the level of breathing zone contaminant and the chemical nature of the contaminant. Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important.

Breathing Zone Level ppm (volume)	Maximum Protection Factor	Half- face Respirator	Full- Face Respirator
1000	10	AX- AUS P	-
1000	50	-	AX- AUS P
5000	50	Airline *	-
5000	100	-	AX- 2 P
10000	100	-	AX- 3 P
	100+		Airline**

\* - Continuous Flow

\*\* - Continuous-flow or positive pressure demand.

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required.

For further information consult site specific CHEMWATCH data (if available), or your Occupational Health and Safety Advisor.

### ENGINEERING CONTROLS

General exhaust is adequate under normal conditions. If risk of overexposure exists, wear SAA approved respirator. Correct fit is essential to obtain adequate protection.

Provide adequate ventilation in warehouse or closed storage areas.

continued...

# POWERS POWERFOAM

Chemwatch Material Safety Data Sheet  
Issue Date: 20-Sep-2006  
NC317ECP

CHEMWATCH 4727-96  
CD 2006/3 Page 10 of 14

## Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

---

## Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

---

### APPEARANCE

Supplied as an aerosol pack. Contents under PRESSURE. Contains highly flammable hydrocarbon propellant. Coloured liquid with a characteristic odour; does not mix with water.

### PHYSICAL PROPERTIES

Liquid.  
Gas.  
Does not mix with water.

Molecular Weight: Not Applicable

Melting Range (°C): Not Available

Solubility in water (g/L): Immiscible

pH (1% solution): Not Available

Volatile Component (%vol): Not Available

Relative Vapour Density (air=1): Not Available

Lower Explosive Limit (%): Not Available

Autoignition Temp (°C): Not Available

State: Liquid

Boiling Range (°C): Not Available

Specific Gravity (water= 1): Not Available

pH (as supplied): Not Available

Vapour Pressure (kPa): Not Available

Evaporation Rate: Not Available

Flash Point (°C): Not Available

Upper Explosive Limit (%): Not Available

Decomposition Temp (°C): Not Available

Viscosity: Not Available

## Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

---

### CONDITIONS CONTRIBUTING TO INSTABILITY

- Elevated temperatures.
- Presence of open flame.
- Product is considered stable.
- Hazardous polymerisation will not occur.

## Section 11 - TOXICOLOGICAL INFORMATION

---

### POTENTIAL HEALTH EFFECTS

#### ACUTE HEALTH EFFECTS

##### SWALLOWED

Not normally a hazard due to physical form of product.

Considered an unlikely route of entry in commercial/industrial environments.

##### EYE

The material may produce severe irritation to the eye causing pronounced inflammation.

Repeated or prolonged exposure to irritants may produce conjunctivitis.

##### SKIN

The material may accentuate any pre-existing dermatitis condition.

Spray mist may produce discomfort.

The material may cause severe skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and

continued...

# POWERS POWERFOAM

Chemwatch Material Safety Data Sheet

Issue Date: 20-Sep-2006

NC317ECP

CHEMWATCH 4727-96

CD 2006/3 Page 11 of 14

Section 11 - TOXICOLOGICAL INFORMATION

thickening of the skin. Repeated exposures may produce severe ulceration.

## INHALED

Inhalation of aerosols (mists, fumes), generated by the material during the course of normal handling, may be harmful.

WARNING: Intentional misuse by concentrating/inhaling contents may be lethal.

Inhalation of high concentrations of gas/vapour causes lung irritation with coughing and nausea, central nervous depression with headache and dizziness, slowing of reflexes, fatigue and inco-ordination.

## CHRONIC HEALTH EFFECTS

Persons with a history of asthma or other respiratory problems or are known to be sensitised, should not be engaged in any work involving the handling of isocyanates. [CCTRADE-Bayer, APMF].

Inhaling this product is more likely to cause a sensitisation reaction in some persons compared to the general population.

Skin contact with the material is more likely to cause a sensitisation reaction in some persons compared to the general population.

Sensitisation may result in allergic dermatitis responses including rash, itching, hives or swelling of extremities.

Respiratory sensitisation may result in allergic/asthma like responses; from coughing and minor breathing difficulties to bronchitis with wheezing, gasping.

Sensitisation may give severe responses to very low levels of exposure, i.e.

hypersensitivity. Sensitised persons should not be allowed to work in situations where exposure may occur.

WARNING: Aerosol containers may present pressure related hazards.

## TOXICITY AND IRRITATION

Not available. Refer to individual constituents.

unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances

### POLYMERIC DIPHENYLMETHANE DIISOCYANATE:

product

Oral (rat) LD50: 43000 mg/kg

Eye (rabbit): 100 mg - mild

Dermal (rabbit) LD50: >9400 mg/kg

Inhalation (rat) LC50: 490 mg/m<sup>3</sup>/4h

The substance is classified by IARC as Group 3:

NOT classifiable as to its carcinogenicity to humans.

Evidence of carcinogenicity may be inadequate or limited in animal testing.

### DIMETHYL ETHER:

TOXICITY

Inhalation (rat) LC50: 308000 mg/m<sup>3</sup>

IRRITATION

Nil Reported

### HYDROCARBON PROPELLANT:

Not available. Refer to individual constituents.

MATERIAL

CARCINOGEN

REPROTOXIN

SENSITISER

SKIN

polymeric  
diphenylmethane  
diisocyanate

IARC:Group 3: Not  
classifiable as to  
carcinogenicity to  
humans

continued...

# POWERS POWERFOAM

Chemwatch Material Safety Data Sheet

Issue Date: 20-Sep-2006

NC317ECP

CHEMWATCH 4727-96

CD 2006/3 Page 12 of 14

Section 11 - TOXICOLOGICAL INFORMATION

## CARCINOGEN

IARC: International Agency for Research on Cancer (IARC) Carcinogens: polymeric diphenylmethane diisocyanate Category: Group 3: Not classifiable as to carcinogenicity to humans

## Section 12 - ECOLOGICAL INFORMATION

Marine Pollutant: Not Determined

Drinking Water Standards:

hydrocarbon total: 10 ug/l (UK max.).

DO NOT discharge into sewer or waterways.

Refer to data for ingredients, which follows:

### POLYMERIC DIPHENYLMETHANE DIISOCYANATE:

Aquatic toxicity:

Fish (Brachydanio rerio) 96h LC0: >1000 mg/l \*

(Daphnia) 24h EC50: >1000 mg/l \*

Bacterial toxicity (activated sludge microorganism) 3h EC50: >100 mg/l \*

\* [Bayer]

### DIMETHYL ETHER:

Water solubility (mg/l): 35300

log Kow (Sangster 1997): 0.1

log Kow: 0.1-0.12

Koc: 14

Half-life (hr) air: 528

Half-life (hr) H2O surface water: 2.6-30

Henry's atm m<sup>3</sup>/mol: 9.78E-04

BCF: 1.7

Bioaccumulation: not sig

processes Abiotic: RxnOH\*

## Section 13 - DISPOSAL CONSIDERATIONS

Treat isocyanate spills with sufficient amounts of isocyanate decontaminant preparation. Typically, such a preparation may consist of: sawdust: 20 parts by weight Kieselguhr 40 parts by weight plus a mixture of {ammonia (s.g. 0.880) 8% v/v non-ionic surfactant 2% v/v water 90% v/v}. Let stand for 24 hours.

- Consult State Land Waste Management Authority for disposal.
- Discharge contents of damaged aerosol cans at an approved site.
- Allow small quantities to evaporate.
- DO NOT incinerate or puncture aerosol cans.
- Bury residues and emptied aerosol cans at an approved site.

## Section 14 - TRANSPORTATION INFORMATION

continued...

# POWERS POWERFOAM

Chemwatch Material Safety Data Sheet  
Issue Date: 20-Sep-2006  
NC317ECP

CHEMWATCH 4727-96  
CD 2006/3 Page 13 of 14

## Section 14 - TRANSPORTATION INFORMATION



Labels Required: FLAMMABLE GAS  
HAZCHEM: 2Y

UNDG:  
Dangerous Goods Class: 2.1 Subrisk: None  
UN Number: 1950 Packing Group: None  
Shipping Name: AEROSOLS

### Air Transport IATA:

ICAO/IATA Class: 2.1 ICAO/IATA Subrisk: None  
UN/ID Number: 1950 Packing Group: None  
ERG Code: 10L  
Shipping Name: Aerosols, flammable

### Maritime Transport IMDG:

IMDG Class: 2 IMDG Subrisk: SP63  
UN Number: 1950 Packing Group: None  
EMS Number: F- D, S- U Marine Pollutant: Not Determined  
Shipping Name: AEROSOLS

## Section 15 - REGULATORY INFORMATION

POISONS SCHEDULE: None

### REGULATIONS

polymeric diphenylmethane diisocyanate (CAS: 9016-87-9) is found on the following regulatory lists;

- Australia High Volume Industrial Chemical List (HVICL)
- Australia Inventory of Chemical Substances (AICS)
- Australia Poisons Schedule
- IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk
- International Agency for Research on Cancer (IARC) Carcinogens
- OECD Representative List of High Production Volume (HPV) Chemicals

dimethyl ether (CAS: 115-10-6) is found on the following regulatory lists;

- Australia Exposure Standards
- Australia Inventory of Chemical Substances (AICS)
- International Council of Chemical Associations (ICCA) - High Production Volume List
- OECD Representative List of High Production Volume (HPV) Chemicals

hydrocarbon propellant (CAS: 68476-85-7) is found on the following regulatory lists;

- Australia Exposure Standards
- Australia High Volume Industrial Chemical List (HVICL)

continued...

# POWERS POWERFOAM

Chemwatch Material Safety Data Sheet

Issue Date: 20-Sep-2006

NC317ECP

CHEMWATCH 4727-96

CD 2006/3 Page 14 of 14

Section 15 - REGULATORY INFORMATION

---

Australia Inventory of Chemical Substances (AICS)  
OECD Representative List of High Production Volume (HPV) Chemicals  
hydrocarbon propellant (CAS: 68476-86-8) is found on the following regulatory lists;  
Australia Inventory of Chemical Substances (AICS)  
OECD Representative List of High Production Volume (HPV) Chemicals

---

## Section 16 - OTHER INFORMATION

---

### INGREDIENTS WITH MULTIPLE CAS NUMBERS

Ingredient Name	CAS
hydrocarbon propellant	68476- 85- 7, 68476- 86- 8

*This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.*

Issue Date: 20-Sep-2006

Print Date: 20-Sep-2006